



BFG3

ACTIVE CARBON FILTER

Fiber filters impregnated with activated carbon powder;
 - Absorption of gases and gaseous substances

- In the interior of air purification
- They are used in chimney type shelter devices.

TYPE	DIMENSIONS		FILTER SURFACE	AIR FLOW	PRESSURE
	A	B	m ²	m ³ /h	(Pa)
BFG3-1	278	287	0,18	710	65
BFG3-2	287	592	0,37	1500	65
BFG3-3	592	592	0,75	3000	65

Dimensions are in (mm). Sound Level Measured from 3m distance in room condition.



BFG4

CASSETTE FILTER

As a pre-filter in all types of ventilation and air conditioning systems. It is used.

TYPE	DIMENSIONS		FILTER SURFACE	AIR FLOW	PRESSURE
	A	B	m ²	m ³ /h	(Pa)
BFG4-1	287	287	0,14	761	80
BFG4-2	287	592	0,29	1570	80
BFG4-3	592	592	0,60	3240	80
BFG4-4	180	287	0,09	478	80
BFG4-5	180	400	0,13	666	80
BFG4-6	264	365	0,17	890	80
BFG4-7	314	505	0,27	1466	80
BFG4-8	365	650	0,32	1704	80
BFG4-9	382	592	0,39	2090	80
BFG4-10	425	650	0,47	2555	80
BFG4-11	465	650	0,52	2800	80
BFG4-12	565	650	0,63	3400	80

Dimensions are in (mm). Sound Level Measured from 3m distance in room condition.

