



opis

Złącze przeciwdrganiowe dedykowane dla wentylatorów kanałowych MAXEE, wyposażone obustronnie w kołnierze montażowe. Wykonane z blachy stalowej galwanizowanej. Dopuszczalna maksymalna temperatura pracy 75°C.

wymiary

Typ	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	m [kg]	nr katalogowy
EXP 315	355	315	8 x 45°	10	120...190	2,9	15424600
EXP 355	395	355	8 x 45°	10	120...190	3,3	15424700
EXP 400	450	400	8 x 45°	12	105...175	3,7	15424800
EXP 450	500	450	8 x 45°	12	105...175	4,5	15424900
EXP 500	560	500	12 x 30°	12	153...223	6,0	15425000
EXP 560	620	560	12 x 30°	12	153...223	6,6	15425100
EXP 630	690	630	12 x 30°	12	153...223	7,4	15425200
EXP 710	770	710	16 x 22,5°	12	255...325	12,5	15425300
EXP 800	860	800	16 x 22,5°	12	255...328	13,2	15760000
EXP 900	970	900	16 x 22,5°	15	245...318	14,9	15761600
EXP 1000	1070	1000	16 x 22,5°	15	245...318	16,5	15763200
EXP 1120	1190	1120	20 x 18°	15	235...308	18,5	15763800
EXP 1250	1320	1250	20 x 18°	15	235...308	20,6	15764500

