



RAS F4

Złącze elastyczne
z klasą odporności ogniowej F400

wymiary

Typ	A [mm]	B [mm]	C	D [mm]	E [mm]	Waga [kg]	nr katalogowy
RAS 315 F4	355	315	8 x 45°	10	120...190	2,7	15429900
RAS 355 F4	395	355	8 x 45°	10	120...190	3,3	15430100
RAS 400 F4	450	400	8 x 45°	12	105...175	3,7	15430200
RAS 450 F4	500	450	8 x 45°	12	105...175	4,5	15430300
RAS 500 F4	560	500	12 x 30°	12	153...223	6,0	15430500
RAS 560 F4	620	560	12 x 30°	12	153...223	6,6	15430600
RAS 630 F4	690	630	12 x 30°	12	153...223	7,4	15430800
RAS 710 F4	770	710	16 x 22,5°	12	255...325	12,5	15430900
RAS 800 F4	860	800	16 x 22,5°	12	255...328	13,2	15769000
RAS 900 F4	970	900	16 x 22,5°	15	245...318	14,9	15769200
RAS 1000 F4	1070	1000	16 x 22,5°	15	245...318	16,5	15769400
RAS 1120 F4	1190	1120	20 x 18°	15	235...308	18,5	15769600
RAS 1250 F4	1320	1250	20 x 18°	15	235...308	20,6	15769900

